


Eaton Cutler-Hammer Safety Switches Heavy-Duty Single Throw with Viewing Window

When ordering specify Catalogue Number



EEMAC 4, 4X and 12/3R
30-800 Ampere

Fusible - 240 VAc, 250 VDc ^{①②}													
System	Amperes	Enclosure		Horsepower Ratings					Dimensions				
		Type 12/3R	Type 4/4X ^③	Ac				Dc	Width	Height	Depth	Mounting	
				Standard Fuse		Time Delay		250 V				A	E
Catalogue #.	Catalogue #	1Ø	3Ø	1Ø	3Ø			B	C	D	E		
	30	12HD321NW	4HD321NW	—	3	—	7-1/2	—	8.14	19.08	11.44	5.50	17.75
	60	12HD322NW	4HD322NW	—	7-1/2	—	15	—	8.14	19.08	11.44	5.50	17.75
	100	12HD323NW	4HD323NW	—	15	—	30	20	11.18	24.95	11.44	8.50	23.62
	200	12HD324NW	4HD324NW	—	25	—	60	—	15.50	35.38	11.63	12.5	33.00
	400	12HD325NW	4HD325NW	—	50	—	125	50	22.66	57.47	12.43	18.00	56.20
	600	12HD326NW	4HD326NW	—	75	—	200	—	23.66	63.00	14.25	19.00	61.75

Fusible - 600 VAc ^{①②}														
System	Amperes	Enclosure		Maximum Hp Ratings with Time Delay Fuses						Dimensions				
		Type 12/3R	Type 4/4X ^③	1Ø Ac		3Ø Ac		Dc		Width	Height	Depth	Mounting	
				480 V	600 V	480 V	600 V	250 V	600 V				A	E
	30	12HD361W	4HD361W	7-1/2	10	15	20	—	—	8.14	19.08	11.44	5.50	17.75
	60	12HD362W	4HD362W	20	25	30	50	—	—	8.14	19.08	11.44	5.50	17.75
	100	12HD363W	4HD363W	30	40	60	75	—	—	11.18	24.95	11.44	8.50	23.62
	200	12HD364W	4HD364W	50	50	125	150	—	—	15.50	35.38	11.63	12.50	33.00
	400	12HD365W	4HD365W	—	—	250	350	—	—	22.66	57.47	12.43	18.00	56.20
	600	12HD366W	4HD366W	—	—	400	500	—	—	23.66	63.00	14.25	19.00	61.75
	800	12HD367W	4HD367W	—	—	500	500	—	—	24.90	71.75	14.25	20.25	70.50

Non-Fusible - 600 VAc, 250 VDc ^{①②}														
System	Amperes	Enclosure		Maximum Hp Ratings with Time Delay Fuses						Dimensions				
		Type 12/3R	Type 4/4X ^③	1Ø Ac		3Ø Ac		Dc		Width	Height	Depth	Mounting	
				480 V	600 V	480 V	600 V	250 V	600 V				A	E
	30	12HD361NFW	4HD361NFW	7-1/2	10	20	30	5	—	8.14	19.08	11.44	5.50	17.75
	60	12HD362NFW	4HD362NFW	20	25	50	60	10	—	8.14	19.08	11.44	5.50	17.75
	100	12HD363NFW	4HD363NFW	30	40	75	100	20	—	11.18	24.95	11.44	8.50	23.62
	200	12HD364NFW	4HD364NFW	50	50	125	150	40	—	15.50	35.38	11.63	12.50	33.00
	400	12HD365NFW	4HD365NFW	—	—	250	350	50	—	22.66	57.47	12.43	18.00	56.20
	600	12HD366NFW	4HD366NFW	—	—	400	500	—	—	23.66	63.00	14.25	19.00	61.75
	800	12HD367NFW	4HD367NFW	—	—	500	500	—	—	24.90	71.75	14.25	20.25	70.50

① Type 12 Enclosures can be modified to meet Type 3R rating when factory provided drain hole is opened.

② For 2 pole applications, use outside poles of 3 pole switch.

③ 30-200 A are stainless steel. 400-800 A are painted steel.

NOTE: 30A, 60A window same as shown in photo. For field replacement window kit in type 12 & 4X order catalogue number 70-8564. For enviroline order catalogue number 70-8564-2.

100A window mounts horizontally. For field replacement window kit in type 12 & 4X order catalogue number 70-8564-4. For enviroline order catalogue number 70-8564-4.

200A to 800A with standard upper viewing window only, new full window does not apply to these ratings. No field replacement kit available.

Window switches with Crouse Hinds or Appleton receptacles will have the new viewing window at 30, 60, 100 ampere available 4th quarter 2003.