



- NOTE:
1. FINISH - GRAY BAKED ENAMEL.
  2. UL LISTED - FILE E-5239-G.
  3. CSA LISTED - FILE 69743.
  4. SUITABLE FOR USE AS SERVICE EQUIPMENT EXCEPT IN CANADA.
  5. NEUTRAL INSULATED, BONDABLE.
  6. 100% LOAD BREAK RATED.
  7. SHORT CIRCUIT CURRENT RATINGS:  
10,000 RMS SYMMETRICAL AMPERES WHEN PROTECTED BY CLASS H OR K FUSES.  
100,000 RMS SYMMETRICAL AMPERES WHEN PROTECTED BY CLASS L OR T FUSES.
  8. DUAL DIMENSIONS, INCHES [MILLIMETERS].

FIELD INSTALLABLE ACCESSORIES	
CAT. NO.	DESCRIPTION
DS16CP	CONTROL POLE
D200EK1	AUXILIARY CONTACT 1 N.O. 1 N.C.
DS200EK2	AUXILIARY CONTACT 2 N.O. 2 N.C.
DS200MH	CONDUIT FITTING 2"
DS250MH	CONDUIT FITTING 2½"
DS300MH	CONDUIT FITTING 3"
DS350MH	CONDUIT FITTING 3½"
DS400MH	CONDUIT FITTING 4"
DS500MH	CONDUIT FITTING 5"
DSLUBKIT	LUBRICATION KIT
DS1200NK	NEUTRAL

APPROXIMATE WEIGHTS	
CAT. NO.	WEIGHT (POUNDS)
DT268JGK	434
DT268JGKN	440
DT368JGK	471
DT368JGKN	477
DT268JRK	436
DT268JRKKN	442
DT368JRK	473
DT368JRKKN	479

TERMINAL LUGS INFORMATION			
LOCATION	MIN. WIRE SIZE	MAX. WIRE SIZE	TYPE
LINE & LOAD LUGS	(4) 1/0 AWG	(4) 750 KCMIL	AL OR CU
NEUTRAL LUGS (3 PROVIDED)	(4) 1/0 AWG	(4) 750 KCMIL	AL OR CU
GROUND LUGS	#6 AWG	250 KCMIL	AL OR CU

REVISION HISTORY	ECO-015441	WARREN SIPE	5/15/2009	95-2088.iam	NEW	<small>EATON CORPORATION - CONFIDENTIAL AND PROPRIETARY THIS DOCUMENT, INCLUDING THE DRAWING AND INFORMATION CONTAINED THEREIN, IS CONFIDENTIAL AND IS THE EXCLUSIVE PROPERTY OF EATON CORPORATION, AND IS BEING FOR YOUR USE ONLY. IT IS NOT TO BE REPRODUCED, COPIED, OR TRANSMITTED IN ANY MANNER WITHOUT THE WRITTEN CONSENT OF EATON CORPORATION. IN THE CASE OF CONTRACTS, CONTRACTUAL PROVISIONS, THIS NOTICE SHALL GOVERN THE STATUS OF THIS DOCUMENT.</small>
	DS1467	PROHASKA	5/15/2009			
	MCS 9/24/10					
	RG 9/24/10					
ADDED NOTE 3 AND "EXCEPT IN CANADA" TO NOTE 4						
DIMENSIONS TO BE INTERPRETED IN ACCORDANCE WITH ASME Y14.5M		SCALE 1=8		PROJECT NO. BD90		
TITLED SAFETY SWITCHES DIMENSION SHEET		DWG NO. 95-2088		SHEET 1 OF 1		
REV. A		PARTS LIST		REV. A		